

- a!
cont -
- (a) providing the object with three independent transmitters of electromagnetic radiation;
 - (b) providing three independent receivers of said electromagnetic radiation, each of said receivers having a fixed position in the reference frame;
 - (c) transmitting said electromagnetic radiation, using said transmitters, a first of said transmitters transmitting said electromagnetic radiation including at least a first frequency, a second of said transmitters transmitting said electromagnetic radiation including at least a second frequency different from said first frequency, and a third of said transmitters transmitting said electromagnetic radiation including at least a third frequency different from said first frequency;
 - (d) receiving signals corresponding to said electromagnetic radiation, at all three of said receivers, at a plurality of times, each of said signals including components of at least one of said three frequencies;
 - (e) for each of said receivers, forming a first function of said components including said components of said signal received by said each receiver from said first transmitter at said first frequency, a second function of said components including said components of said signal received by said each receiver from said second transmitter at said second frequency, and a third function of said components including said components of said signal received by said each transmitter from said third transmitter at said third frequency, said functions being independent of a time delay between said transmitters and said receivers; and

a1
comb.

- (f) inferring the position and the orientation of the object from said functions.

a2

9. (Amended) The method of claim 7, wherein each of said signals including components of at least one of said three frequencies, the method further comprising the step of:

- (f) for each of said receivers, forming a first function of said components including said components of said signal received by said each receiver from said first transmitter at said first frequency, a second function of said components including said components of said signal received by said each receiver from said second transmitter at said second frequency, and a third function of said components including said components of said signal received by said each transmitter from said third transmitter at said third frequency, said functions being independent of a time delay between said transmitters and said receivers;

said position and orientation of the object being inferred from said functions.

REMARKS

Reconsideration of the above-identified patent application in view of the amendments above and the remarks following is respectfully requested.

Claims 1-14 are in this case. Claims 1-9 have been rejected under § 102(e). Claims 10-14 have been rejected under § 103(a). Independent claim 1 and dependent claim 9 have been amended.

~~28~~ 27

A